




INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶ : H04Q 7/36	A1	(11) International Publication Number: WO 97/14259 (43) International Publication Date: 17 April 1997 (17.04.97)
(21) International Application Number: PCT/US96/16898 (22) International Filing Date: 15 October 1996 (15.10.96)	(81) Designated States: AU, CA, CN, FI, JP, KR, European patent (AT, BE, CH, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE).	
(30) Priority Data: 08/542,720 13 October 1995 (13.10.95) US (71) Applicant: AIRNET COMMUNICATIONS CORPORATION [US/US]; Suite 300, 100 Rialto Place, Melbourne, FL 32901 (US). (72) Inventor: DONER, John, R.; 611 N. Marlin Circle, Sebastian, FL 32976 (US). (74) Agents: THIBODEAU, David, J., Jr. et al.; Hamilton, Brook, Smith & Reynolds, P.C., Two Militia Drive, Lexington, MA 02173 (US).	Published <i>With international search report. Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.</i>	

(54) Title: A METHOD FOR FREQUENCY ALLOCATION AND ASSIGNMENT IN WIRELESS COMMUNICATION SYSTEMS

(57) Abstract

A single-cell wireless communication system is partitioned into n sectors, to which channels are allocated from two groups of non-adjacent channels. If the available channels are consecutively numbered from lowest to highest frequency, or vice versa, the groups are, respectively, the even-numbered channels and the odd-numbered channels. These two groups are each subdivided into $n/2$ sets, with the first set of each group including the lowest numbered channels of the group, the next set including the next lowest-numbered channels of the group, and so forth. The sets are then allocated to the sectors such that the first set of one of the groups is allocated to a first sector, the next set of the same group is allocated to a contiguous sector and so forth, with the last set of the second group allocated to the n th sector. The dividing points between the sets are selected such that any sector has at most a single channel that may experience adjacent-channel interference from a channel that is allocated from a contiguous sector. Preferably, a channel is selected for assignment to the mobile units such that the selected channel is within a greatest gap between the channels of the same set that are then in use. If the selected channel is the one channel that may experience adjacent-channel interference, another channel may be selected from the set.



FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AM	Armenia	GB	United Kingdom	MW	Malawi
AT	Austria	GE	Georgia	MX	Mexico
AU	Australia	GN	Guinea	NE	Niger
BB	Barbados	GR	Greece	NL	Netherlands
BE	Belgium	HU	Hungary	NO	Norway
BF	Burkina Faso	IE	Ireland	NZ	New Zealand
BG	Bulgaria	IT	Italy	PL	Poland
BJ	Benin	JP	Japan	PT	Portugal
BR	Brazil	KE	Kenya	RO	Romania
BY	Belarus	KG	Kyrgyzstan	RU	Russian Federation
CA	Canada	KP	Democratic People's Republic of Korea	SD	Sudan
CF	Central African Republic			SE	Sweden
CG	Congo	KR	Republic of Korea	SG	Singapore
CH	Switzerland	KZ	Kazakhstan	SI	Slovenia
CI	Côte d'Ivoire	LI	Liechtenstein	SK	Slovakia
CM	Cameroon	LK	Sri Lanka	SN	Senegal
CN	China	LR	Liberia	SZ	Swaziland
CS	Czechoslovakia	LT	Lithuania	TD	Chad
CZ	Czech Republic	LU	Luxembourg	TG	Togo
DE	Germany	LV	Latvia	TJ	Tajikistan
DK	Denmark	MC	Monaco	TT	Trinidad and Tobago
EE	Estonia	MD	Republic of Moldova	UA	Ukraine
ES	Spain	MG	Madagascar	UG	Uganda
FI	Finland	ML	Mali	US	United States of America
FR	France	MN	Mongolia	UZ	Uzbekistan
GA	Gabon	MR	Mauritania	VN	Viet Nam

A METHOD FOR FREQUENCY ALLOCATION AND ASSIGNMENT IN WIRELESS COMMUNICATION SYSTEMS

FIELD OF THE INVENTION

This invention relates generally to wireless radio frequency communication systems and in particular to a technique for assigning frequencies to mobile units.

BACKGROUND OF THE INVENTION

The ever-increasing demand for wireless communication services, such as cellular mobile telephone, digital cellular network, personal communications services and the like, requires the operators of such systems to attempt to make maximum effective use of available radio frequency bandwidth. A system operator is typically allocated a geographic territory, and a certain amount of bandwidth that affords the ability to transmit and receive on a particular number of different channel frequencies (referred to hereinafter as "channels") within that territory. In an effort to make the best use of the available frequency space, a large geographic territory is typically divided into a number of sub-areas called cells. Each cell includes an associated base station and an antenna that together handle communications with mobile units within the cell. Each area covered by an antenna, and thus, each cell, is considered a single coverage area.

Once the geographic territory is divided into cells, the system operator allocates the available channels among the cells, or coverage areas, so as to minimize adjacent-channel interference and, also, to minimize co-channel interference. To do this, the operator typically allocates non-adjacent channels to a single coverage area. If, for example, the available channels are consecutively numbered from lower frequencies to higher frequencies, or vice versa, a cell is allocated every other channel, i.e. the odd-numbered or the even-numbered channels. Under this scheme, a geographic territory serviced by a single cell is allocated a set of non-adjacent channels, which is one-half of the spectral allocation. Accordingly, only one-half of the channels available to the system operator are made available to the mobile units.

To further increase channel availability, the cell may be subdivided into a number of sectors, with each sector serviced by an associated directional antenna. Each sector is thus considered a single service area, which means that each sector has allocated to it a subset of the available channels. Accordingly, in a cell that has three sectors, the first sector may be allocated channels 1, 4, 7 and so forth; a second sector allocated channels 2, 5, 8 and so forth; and a third sector allocated channels 3, 6, 9 and so forth. Thus each sector is allocated a group of channels modulo "n", where n is the number of sectors. This ensures that each sector is allocated a set of non-adjacent channels.

A problem with adjacent-channel interference arises at the sector boundaries, however. Each antenna provides strong signals throughout the entire associated sector, and thus, at the boundaries between, for example, the first and second sectors, communications on adjacent channels 1 and 2, 4 and 5 and so forth may interfere. Similarly, at the boundary between the first and third sectors, communications on adjacent channels 4 and 3, 7 and 6, and so forth may interfere. This scheme results in a large portion of the cell being subject to strong adjacent-channel interferences.

SUMMARY OF THE INVENTION

The invention is a single-cell wireless communication system that utilizes all of the spectral allocation available to the system operator by allocating channels to cell sectors from two subdivided groups of non-adjacent channels. The minimum number of sectors is four.

More specifically, the channels in the spectral allocation are consecutively numbered, from lower to higher frequencies, or vice versa, and divided into two groups of non-adjacent, namely, the odd-numbered channels, S_O and the even-numbered channels S_E . If there are four sectors, the S_O group of channels is further subdivided into 4/2, or two sets, S_{OL} and S_{OH} , which contain, respectively, the lower half and the upper half of the odd-numbered channels. The S_E group of channels are similarly subdivided into two sets, S_{EL} and S_{EH} , which contain, respectively, the lower half and the upper half of the even-numbered channels. The four subsets of channels are then allocated to the four sectors so as to minimize the assignment of adjacent channels to contiguous sectors. For example, if the sectors are numbered clockwise from 1 to 4, and sector one is allocated the S_{EL} set of channels, sector two is allocated the S_{EH} set of

channels, sector three is allocated the S_{OL} set of channels and sector four is allocated the S_{OH} set of channels. As discussed in more detail below, the dividing points between the sets are chosen such that there is at most one channel in any sector that may experience adjacent-channel interference at a sector boundary.

For a cell with more than four sectors, the two groups S_E and S_O are each divided into $n/2$ sets of lowest to highest-numbered channels, where "n" is the number of sectors. The sets are then allocated to the sectors by allocating to the first set of one of the groups to the first sector, the second set of the same group to the second sector, and so forth, with the last set of the second group allocated to the nth sector.

In a preferred embodiment of the invention, channels within a sector are assigned to mobile units in accordance with a technique that I refer to as the "greatest gap" technique. Using this technique, the base station determines which of the allocated channels are currently unused, or free. It then determines which of these free channels are included in the largest group of "contiguous," that is, contiguous within the set, channels. In the S_{EL} set, for example, if channels 6, 8, 10, 16, 18 and 24 are currently free, the largest group of contiguous unused channels consists of channels 6, 8 and 10. This contiguous group may be thought of as a "gap" between channels that are currently in use. In the example, the greatest gap is between channels 4 and 12. Other gaps in the set consist of channels 2 and 4, and channels 16 and 18. The base station then selects for assignment to the mobile unit the channel that is in the middle of the greatest gap.

If the selected channel is one that could result in adjacent-channel interference at one of the sector boundaries, the base station may first determine if the adjacent channel in the contiguous sector is in use. If that channel is in use, the base station then selects another channel to assign to the mobile unit. The base station may select this channel from the greatest gap or from another gap, as appropriate.

Alternatively, the base station may select another channel for assignment to the mobile unit regardless of whether or not the adjacent channel is in use in the contiguous sector.

BRIEF DESCRIPTION OF THE DRAWINGS

The above and further advantages of the invention may be better understood by referring to the following description in conjunction with the accompanying drawings, in which:

Fig. 1 is a block diagram of a wireless communication system according to the invention;

Fig. 2 is a block diagram of a base station included in the system of Fig. 1;

Fig. 3 is a schematic diagram of the system of Fig. 1 that depicts the channel allocation scheme that is used in the system of Fig. 1; and

Fig. 4 is a flow chart of the operations of the base station of Fig. 2 when the system is operating in accordance with the greatest gap technique.

DETAILED DESCRIPTION OF ILLUSTRATIVE EMBODIMENTS

Referring now to Fig. 1, a cellular communication system 10 consists of a single cell 12 that is partitioned into a minimum of $n=4$ sectors 14. Such an arrangement is suitable, for example, for a system that services an island or other isolated area.

As depicted in the drawing, the cell 12 is partitioned into four ninety-degree sectors 14. The cell 12 includes a centrally-located base station 16 that has a plurality of directional antennas 18a-d, which are arranged such that each antenna 18 services an associated sector 14.

A mobile telephone exchange 20, which operates in a conventional manner, provides connections between the base station 16 and a public switched telephone network (PSTN) 22. The system thus allows mobile units 20 within the cell 12 to communicate with each other or with other devices that may be connected to the PSTN 22. To simplify the drawing connections between the mobile telephone exchange 20 and the PSTN 22 are not shown.

Referring also to Fig. 2, the base station 16 is depicted in more detail. The four directional antennas 18a-d, which each, respectively, handle communications between mobile units within their associated sectors 14, are connected to corresponding multichannel transceivers 24a-d. The transceivers 24a-d operate in a conventional manner in conjunction with a base station controller 26, to provide filtering, modulation and demodulation functions that are necessary to couple radio signals received from the mobile units 20 to the PSTN 22, and conversely, to forward signals from the PSTN 22 to the mobile units 20.

An optional omni-directional antenna 23 may be connected to a control-signal receiver 28, to permit the transmission and reception of control signals between the base station controller 26 and the mobile units 20 that are located anywhere within the cell 12. In response to the receipt of control signals that request a channel assignment, the control-signal receiver 28 determines in which sector 14 the requesting mobile unit 20 is located, and assigns to the unit a channel that is allocated to that sector. The receiver 28 then arranges for the appropriate transceiver 24a-d and antenna 18a-d to handle further communications with the mobile unit. In a preferred embodiment, the control-signal receiver assigns channels to the mobile units in accordance with a "greatest gap" technique, as discussed below with reference to Fig. 4.

Referring now to Fig 3, the channel allocations to the sectors 14 are made so as to minimize adjacent-channel interference. The channels in the spectral allocation available to the system are consecutively numbered, from the lowest frequencies to highest frequencies or vice versa. The channels are then grouped into two groups of non-adjacent channels, such as even-numbered channels, S_E , and odd-numbered channels, S_O . Next, the two groups are subdivided into $n/2$ sets of higher and lower frequencies. Thus, for $n=4$, the group of S_E channels are subdivided into two sets of higher and lower frequencies, namely, S_{EH} and S_{EL} , and the group of S_O channels are also subdivided into two sets of higher and lower frequencies, namely, S_{OH} and S_{OL} . As explained below, the dividing points of the groups into sets are chosen and the four sets of channels are allocated to the sectors 14 such that contiguous sectors include at most one channel that may experience adjacent-channel interference.

If the sectors are numbered clockwise from 1 to 4, sector 1 is allocated the S_{EL} set of channels, sector two is allocated the S_{EH} set of channels, sector three is allocated the S_{OL} set of channels and sector four is allocated the S_{OH} set of channels. There are no adjacent channels in

sectors 1 and 2, or 3 and 4, and thus, there is no adjacent-channel interference at the respective boundaries between these sectors. The dividing points between the S_{EL} and S_{EH} sets, and S_{OL} and S_{OH} sets are appropriately chosen such that there is at most a potential for adjacent-channel interference between communications over a single channel between sectors 1 and 4, or sectors 2 and 3. The sets are thus divided such that the highest-numbered channel in, for example, the S_{EL} set is adjacent to the lowest-numbered channel in the S_{OH} set, or the lowest-numbered channel in S_{EH} set is adjacent to the highest-numbered channel in the S_{OL} set. Accordingly, there is a minimum amount of adjacent-channel interference between the sectors.

If, for example, the odd-numbered channels are divided such that channel 41 is the lowest-numbered channel in sector 4, the even numbered channels should be divided such that S_{EL} has channel 40 as its highest-numbered channel. Otherwise, communications on the channels of sector 1 may interfere with more than one channel in sector 4. If the dividing point between the high and low sets of the even-numbered channels was instead chosen such that the highest-numbered channel in S_{EL} is channel 42, there could be interference between that channel and two channels in sector 4, namely, channels 41 and 43.

If n is odd, that is, if the cell 12 is partitioned into an odd number of sectors, the two groups of non-adjacent channels S_O and S_E , are divided such that one group has $n/2$ sets, where $^{\circ}$ represents an integer value. The other group is then divided into $n/2+1$ sets. The first sets of each group include the lowest-numbered channels in the group, the next sets include the next lowest-numbered channels in the group and so forth, with the last sets of the groups including the highest-numbered channels. The sets are then allocated to the sectors in clockwise order, with the first set of one of the groups allocated to sector 1, the next set of the same group allocated to sector 2 and so forth, and the last set of the second group allocated to sector n . In this cell, only the sectors that have been allocated the first or last sets of a group may experience adjacent-channel interference at one of their sector boundaries.

With an odd number of sectors, differences in the number of channels that are allocated to the various sectors can be compensated for by allocating fewer channels to the sectors that cover areas with lower population densities, or by changing the sizes of the sectors that have fewer channels allocated to them.

Referring now to Fig. 4 in conjunction with Figs 1 and 3, I discuss a preferred technique for assigning channels to the mobile units. When a mobile unit 20 requests a connection, the base station first determines which sector 14 the mobile unit is in (step 100). In this example, the mobile unit 20 is located in sector 1. Next, the base station 16 determines which of the channels allocated to sector 1 are not in use, and further determines which of these channels are included in the greatest "gap" between channels that are then in use (step 102). If sector 1 has allocated to it channels 2, 4, 6...40, and channels 6, 8, 10, 16, 18 and 24 are currently free, the largest group of unused channels that are contiguous within the set consists of channels 6, 8 and 10. These channels constitute the greatest gap between channels that are then in use. The base station may determine which channels are free by consulting a table (not shown) or by scanning the channels.

The base station then selects for assignment to the mobile unit the channel that is in the middle of the greatest gap (step 104). The base station thus selects channel 8. If the selected channel is the one channel that may result in adjacent-channel interference at a sector boundary, the base station determines if the adjacent channel in the contiguous sector is in use (steps 106, 108). If the adjacent channel is not in use, the base station assigns the selected channel, that is, channel 8, to the unit (step 110). Otherwise, the base station refrains from assigning the selected channel to the unit and instead assigns to the unit another of the free channels (steps 112, 114). The base station may select this channel from the greatest gap, or from any other gap. In this way, the base station avoids a potential problem with adjacent-channel interference.

Alternatively, the base station may select another channel for assignment to the mobile unit, without first determining if the adjacent channel is in use.

The foregoing description has been limited to a specific embodiment of this invention. It will be apparent, however, that variations and modifications may be made to the invention, with the attainment of some or all of its advantages. Therefore, it is the object of the appended claims to cover all such variations and modifications as come within the true spirit and scope of the invention.

What is claimed is:

CLAIMS

1. A method for allocating channels to sectors of a cell of a wireless communication system, the method including the steps of:

- A. partitioning the cell into n sectors;
- B. consecutively numbering the channels, from lowest to highest frequency, and grouping the numbered channels into a first group and a second group of non-adjacent channels;
- C. subdividing each of the first and second groups into $n/2$ sets of channels, with a first set of each group containing the lowest-numbered channels of the associated group, the second set containing the next lowest-numbered channels of the associated group, and so forth;
- D. assigning the first set of the first group of channels to a first sector of the cell;
- E. assigning to a contiguous sector of the cell the second set of the first group;
- F. assigning to a next contiguous sector of the cell the next set of the first group;
- G. repeating step F until all of the sets of the first group are assigned to sectors;
- H. assigning the first set of the second group to a next contiguous sector; and
- I. repeating step F for the sets of the second group.

2. The method of claim 1, where the cell is partitioned into four cells, the channels are grouped into groups of even-numbered and odd-numbered channels, and the groups are subdivided into sets of even-numbered high and low channels and odd-numbered high and low channels.

3. A method for assigning to a mobile unit channels that are allocated to sectors of a cell in a wireless communication system, the method including the steps of:

- A. determining the sector in which a mobile unit that is requesting a channel assignment is located;
- B. determining unused channels that are allocated to the sector in which the mobile unit is located;
- C. determining which of the unused channels are associated with a greatest gap between channels that are in use;

D. selecting the channel that is in the middle of the greatest gap and assigning the selected channel to the mobile unit.

4. The method of claim 3 further including the steps of:

- i. determining if the selected channel is adjacent to a channel that is allocated to a contiguous sector;
- ii. assigning to the mobile unit another channel that is not adjacent to a channel in the contiguous sector; or
- iii. if the selected channel is not adjacent to a channel that is allocated to a contiguous sector assigning the selected channel to the mobile unit.

5. The method of claim 4 wherein the step of assigning another channel to the mobile unit includes assigning to the unit another channel from the greatest gap.

6. The method of claim 3 further including the steps of:


- i. determining if the selected channel is adjacent to a channel that is allocated to a contiguous sector;
- ii. determining if the adjacent channel is in use in the contiguous sector;
- iii. if the adjacent channel is in use, selecting another channel and assigning the channel to the mobile unit; and
- iv. if the adjacent channel is not in use, assigning the selected channel to the mobile unit.

7. The method of claim 6 wherein the step of selecting another channel includes selecting another channel from the greatest gap.

8. The method of claim 6 wherein the step of selecting another channel includes determining other gaps in the used channels and selecting another channel from a gap other than the greatest gap.


1/4

FIG. 1




2/4

FIG. 2




3/4

FIG. 3



4/4

FIG. 4



INTERNATIONAL SEARCH REPORT

Internat Application No
PCT/US 96/16898

A. CLASSIFICATION OF SUBJECT MATTER

IPC 6 H04Q7/36

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 6 H04Q

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	US 5 257 398 A (SCHAEFFER DENNIS R) 26 October 1993 see column 2, line 6 - column 2, line 47; figures 1,3 ---	1,2
A	EP 0 616 481 A (NIPPON ELECTRIC CO) 21 September 1994 see column 15, line 23 - column 17, line 57; figures 9,10 ---	1,2
A	MANGINI D M: "Frequency coordination of cellular systems", 37TH IEEE VEHICULAR TECHNOLOGY CONFERENCE: QUALITY REQUIRES WORK (CAT. NO.87CH2429-9), TAMPA, FL, USA, 1-3 JUNE 1987, 1987, NEW YORK, NY, USA, IEEE, USA, PAGE(S) 312 - 317 XP002024055 see page 314, line 2 - line 16 --- -/-	1,2

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

* Special categories of cited documents:

- *A* document defining the general state of the art which is not considered to be of particular relevance
- *E* earlier document but published on or after the international filing date
- *L* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- *O* document referring to an oral disclosure, use, exhibition or other means
- *P* document published prior to the international filing date but later than the priority date claimed

- *T* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- *X* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- *Y* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art
- *&* document member of the same patent family

Date of the actual completion of the international search

29 January 1997

Date of mailing of the international search report

17.03.97

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax (+31-70) 340-3016

Authorized officer

Schut, G

INTERNATIONAL SEARCH REPORT

Intern: al Application No
PCT/US 96/16898

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	<p>INTERNATIONAL CONFERENCE ON UNIVERSAL PERSONAL COMMUNICATIONS, vol. 2, 12 October 1993, pages 718-722, XP000570284 FARUQUE S: "THE N=9 FREQUENCY PLAN: A MODIFIED TECHNIQUE TO ENHANCE C/I PERFORMANCE AND CAPACITY" see paragraph 2.2</p> <p style="text-align: center;">-----</p>	1,2

INTERNATIONAL SEARCH REPORT

International application No.

PLI/US 96/16898

Box I Observations where certain claims were found unsearchable (Continuation of item 1 of first sheet)

This International Search Report has not been established in respect of certain claims under Article 17(2)(a) for the following reasons:

1. ☐ Claims Nos.:
because they relate to subject matter not required to be searched by this Authority, namely:
2. ☐ Claims Nos.:
because they relate to parts of the International Application that do not comply with the prescribed requirements to such an extent that no meaningful International Search can be carried out, specifically:
3. ☐ Claims Nos.:
because they are dependent claims and are not drafted in accordance with the second and third sentences of Rule 6.4(a).

Box II Observations where unity of invention is lacking (Continuation of item 2 of first sheet)

This International Searching Authority found multiple inventions in this international application, as follows:

see extra sheet

1. ☐ As all required additional search fees were timely paid by the applicant, this International Search Report covers all searchable claims.
2. ☐ As all searchable claims could be searched without effort justifying an additional fee, this Authority did not invite payment of any additional fee.
3. ☐ As only some of the required additional search fees were timely paid by the applicant, this International Search Report covers only those claims for which fees were paid, specifically claims Nos.:
4. ☒ No required additional search fees were timely paid by the applicant. Consequently, this International Search Report is restricted to the invention first mentioned in the claims; it is covered by claims Nos.:

1,2

Remark on Protest

- ☐ The additional search fees were accompanied by the applicant's protest.
- ☐ No protest accompanied the payment of additional search fees.

INTERNATIONAL SEARCH REPORT

International Application No. PCT/US 96/ 16898

FURTHER INFORMATION CONTINUED FROM PCT/ISA/210

1. claims 1,2:

Reduction of adjacent channel interference between contiguous sectors in a cell

2. claims 3-8:

Finding a new channel in a sector with reduced adjacent channel interference between the new channel and already used channels within the sector

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/US 96/16898

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
US 5257398 A	26-10-93	CA 2073241 A,C	28-08-91
		CN 1054517 A	11-09-91
		EP 0517828 A	16-12-92
		HR 940220 A	31-10-96
		IL 97285 A	24-06-94
		JP 5503624 T	10-06-93
		KR 9604445 B	03-04-96
		WO 9113521 A	05-09-91
EP 0616481 A	21-09-94	JP 6276138 A	30-09-94
		JP 7044725 B	15-05-95

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☒ **BLACK BORDERS**
- ☐ **IMAGE CUT OFF AT TOP, BOTTOM OR SIDES**
- ☐ **FADED TEXT OR DRAWING**
- ☐ **BLURRED OR ILLEGIBLE TEXT OR DRAWING**
- ☐ **SKEWED/SLANTED IMAGES**
- ☒ **COLOR OR BLACK AND WHITE PHOTOGRAPHS**
- ☐ **GRAY SCALE DOCUMENTS**
- ☒ **LINES OR MARKS ON ORIGINAL DOCUMENT**
- ☐ **REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY**
- ☐ **OTHER:** _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.

THIS PAGE BLANK (USPTO)